Using Central Nodes for Efficient Data Collection in Wireless Sensor Networks

Vitaly Milyeykovski^a, Michael Segal^a, Hanan Shpungin^b, Vladimir Katz^a

^aCommunication Systems Engineering Department, Ben-Gurion University of the Negev, Israel. Email: {milyeyko,segal}@bgu.ac.il

^bDepartment of Electrical Computer Engineering, University of Waterloo, Waterloo, Canada. Email: hanan.shpungin@uwaterloo.ca

Abstract

We study the problem of data collection in Wireless Sensor Networks (WSN). A typical WSN is composed of wireless sensor nodes that periodically sense data and forward it to the base station in a multi-hop fashion. We are interested in designing an efficient data collection tree routing, focusing on three optimization objectives: energy efficiency, transport capacity, and hop-diameter (delay).

In this paper we develop single- and multi-hop data collection, which are based on the definition of node centrality: centroid nodes. We provide theoretical performance analysis for our approach, present its distributed implementation and discuss the different aspects of using it. Most of our results are for two-dimensional WSNs, however we also show that the centroid-based approach is asymptotically optimal in three-dimensional random node deployments. In addition, we present new construction for arbitrary network deployment based on central nodes selection. We also present extensive simulation results that support our theoretical findings.

1. Introduction

A wireless sensor network (WSN) consists of small autonomous low-cost low-power devices that carry out monitoring tasks. Initially developed for military use, WSNs can nowadays be found in many civil applications, such as environmental monitoring, biomedical research, seismic monitoring, and precision agriculture [1]. The devices are called *sensor nodes* and the monitored data is typically collected at a *base station*, following a specific collection pattern of activated wireless links.

As these networks have no hard-wired underlying topology, one of the most fundamental issues when a WSN is deployed is the formation of an efficient communication backbone, or in other words, answering the question *which links to use in order to collect the data from the sensor nodes?*

Efficiency can be defined in many ways, for example it can be maximizing the rate at which data is collected ([23, 44, 46]) from the sensor nodes, prolonging the network lifetime by reducing the energy consumption ([6, 9, 33, 35, 39]), minimizing the number of hops from the sensor nodes to the collecting base station ([16, 22]), and other optimization objectives. It is apparent that the *topological structure of the communication backbone* plays a vital role in its efficiency. However, it is also important to note that a communication backbone which has good performance in some of the criteria can have a bad one in others. For example, using the minimum spanning tree (MST) as the backbone provides an optimal network lifetime performance for same initial battery charges

Preprint submitted to Elsevier

June 6, 2015

[5], however it can have a very poor hop-diameter, which is critical for delay minimization.¹ Thus,² the network designer has to take special care when deciding which links to activate for the purpose of data collection, as different optimization objectives may be have a negative effect on each other.

The problem of data collection can be divided into two major paradigms. Data collection with aggregation ([25, 42]) allows each sensor node to accumulate the messages of its descendants and then pass only one fixed-size message towards the base station. The second paradigm, is data gathering without aggregation ([29, 30]) which requires that all messages initiated by the sensors will eventually reach the base station.

Our main objective in this paper is to construct efficient communication backbones for singleand multi-hop data collection with aggregation in WSNs for random sensor node deployments, while measuring the efficiency based on the next three metrics.

- The *transport capacity* metric represents the sum of rate-distance products over all the active links. It is measured in *bit-meters* and was first introduced by [20]. The idea behind this measure is to capture both the notion of the overall rate and distance that the information travels in a network.
- *Hop-diameter* is another important metric which reflects the depth of the data gathering tree, i.e. the maximum number of hops from any of the sensor nodes to the base station.
- Total energy consumption is probably one of the most important parameters of a WSN as the sensor nodes are often deployed in areas where battery replacement is infeasible [8]. Wireless communication is a major contributer to the energy budget of a node. In this paper we focus on minimize the total energy consumed by all nodes for communication purposes.

We propose a novel approach for the construction of communication backbones by identifying *central locations* in the deployment area and routing all data through these regions. The general idea is that these locations would serve as aggregation points both on a local and global scale. In particular, we use an interesting geometrical notion of *centroids*, which is defined as the central geometrical position of a collection of nodes, which are used as a guide for the construction of hierarchical aggregation trees.

The rest of this paper is organized as follows. In Section 2 we present our system settings and state our objective. Related works are surveyed in Section 3. Sections 4 and 5 are the technical sections of the paper and show the construction of data collection communication backbones for three scenarios, single-hop general network and multiple-hop random network. We present additional construction for arbitrary network deployment based on central nodes selection in Section 6. Simulation results for various types of networks are presented in Section 7 and compared to the results of similar spirit obtained in [14]. Finally, we conclude and discuss future work in Section 8.

2. System settings

A WSN consists of n wireless sensor nodes, $S = \{s_1, \ldots, s_n\}$, distributed in some area A. These nodes perform monitoring tasks and periodically report to a base station r which is located somewhere within the area A (we consider different locations throughout the paper). During the

¹Imagine n sensor nodes located on a straight horizontal segment, with the base station being to the right of the right-most sensor. It is easy to show that the hop-diameter of MST in this case is n.

report phase, the sensor nodes propagate a message to the base station through a data collection \dot{n} tree, $T_S = (S \cup \{r\}, E_S)$, rooted at r. We consider data collection with aggregation, where every node $s \in S$ forwards a single unit size report message to its parent. The message holds an accumulated information collected from a subtree of T_S rooted at s. An example of this scenario can be found in temperature monitoring systems for fire prevention, intrusion detection, seismic readings, etc.

We assume the use of *frame-based* MAC protocols (see [10]) which divide the time into frames, containing a fixed number of slots. The main difference from the classic TDMA is that instead of having one access point which controls transmission slot assignments, there is a localized distributed protocol mimicking the behavior of TDMA. The advantage of a frame-based (TDMA-like) approach compared to the traditional IEEE 802.11 (CSMA/CA) protocol for a Wireless LAN is that collisions do not occur, and that idle listening and overhearing can be drastically reduced. When scheduling communication links, that is, specifying the sender-receiver pair per slot, nodes only need to listen to those slots in which they are the intended receiver – eliminating all overhearing. When scheduling senders only, nodes must listen in to all occupied slots, but can still avoid most overhearing by shutting down the radio after the MAC (slot) header has been received. In both variants (link and sender-based scheduling) idle listening can be reduced to a simple check if the slot is used or not. Several MAC protocols were developed to adapt classical TDMA solutions which use access points to ad-hoc settings that have no infrastructure; these protocols employ a distributed slot-selection mechanism that self-organizes a multi-hop network into a conflict-free schedule (see [34, 45]).

Let d(u, v) be the Euclidean distance between two sensor nodes $u, v \in S$. It is customary to estimate that the energy required to transmit from u to v is proportional to $d(u, v)^{\alpha}$, where α is the *path-loss coefficient*. In perfect conditions $\alpha = 2$, however in more realistic settings (in presence of obstructions or noisy environment) it can have a value between 2 and 4 (see [32]). In this paper we assume $\alpha = 2$ for simplicity. However, it is possible to extend our results for other values of α which are greater than 2.

Let $E(T_S)$ be the **energy requirement** to execute a single report phase. Note that every sensor performs a single transmission, during which it sends a single message to its parent in T_S . Thus, the energy requirement is proportional to the sum of squares of lengths of the edges $E(T_S)$. The focus of this paper is to study the asymptotic performance of data collection trees, thus we can express $E(T_S)$ as follows, $E(T_S) = \sum_{(u,v) \in E_S} d(u,v)^2$.

Minimizing the energy requirement is one of the primary optimization objectives when deploying a WSN due to the very low battery reserves at the sensor nodes and the high costs that are associated with replacing these batteries (if at all possible).

Another critical aspect in the design of a WSN is the **hop-diameter** of T_S . The data flows from the leafs of the delivery tree to the base station, where each intermediate node waits to receive the report messages from all its children, before sending its own report message to its parent. Therefore, the hop-diameter of T_S , denoted as $H(T_S)$, determines the delay of data collection.

The third measure that we are interested in is **transport capacity**, $D(T_S)$, of the data collection tree T_S . As mentioned earlier, the main idea which stands behind this metric is to capture the spatial rate of the network, which is represented by the total rate over some distance. In our scenario, the rate on all links is fixed as all the nodes transmit an aggregated, unit-size message, to the parent in the collection tree and the schedule is conflict-free. Thus, to maximize the transport capacity we need to minimize the total distance traveled by information, which is the sum of lengths of all the links, $D(T_S) = \sum_{(u,v) \in E_S} d(u, v)$.

Unfortunately it is impossible to achieve optimal performance in all three measures at the same

time. For example, minimizing the hop-diameter results in all nodes transmitting to the bas⁴ station, which is disastrous in terms of energy consumption, whereas the best topology to minimize energy consumption² results in a relatively high hop-diameter.

Our main objective in this paper is to construct data collection trees for several node distribution scenarios which produce good performance in all three measures simultaneously.

3. Related work

This work is a continuation of works [14, 16] which take into account all of the above 3 performance measures simultaneously. Below we discuss some of the related work on data collection, energy efficiency, bounded-hop communication, and transport capacity.

In terms of **total energy consumption** measure, it was proved in [38] that using the minimum spanning tree for data collection (gathering) with aggregation achieves optimality. A different criterion used to measure energy efficiency is network lifetime, which is defined as the time the first node depletes all its power reserves due to periodic data transmission. Segal [37] developed an optimal maximum lifetime algorithm for data collection with aggregation. One of the possible variants is to allow the use of different collection trees, which makes the maximum network lifetime data gathering problem more challenging. Interestingly, if aggregation is allowed, the problem is still polynomially solvable [25, 31], and is NP-complete otherwise [30]. Kalpakis et. al. [25] developed an optimal data collection with aggregation algorithm in $O(n^{15} \log n)$ time. To counter the slowness of the algorithm, Stanford and Tongngam [42] proposed a $(1 - \varepsilon)$ -approximation in $O(n^{3}\frac{1}{\varepsilon}\log_{1+\varepsilon} n)$ time based on Garg and Könemann [19]. For more details we refer the reader to a recent survey by Ramanan et al. [27], which covers a diverse set of data gathering algorithms in ad-hoc networks.

The notion of **transport capacity** was introduced by Gupta and Kumar in [20]. They showed that for any layout of n wireless nodes in an area of size A, with each node being able to transmit Wbits per second to a fixed range, the overall transport capacity is at most $(W\sqrt{An})$ bit-meters per second under both interference models (protocol and physical). In [24] the authors derive upper bounds on the transport capacity as a function of the geographic location of the nodes. It has also been shown that the scaling of transport capacity depends, among other factors, on channel attenuation and path loss [47, 48, 49].

Finally, communication backbones with **bounded hop-distances** between participating nodes has also been studied. For the linear layout of nodes and an upper bound on hop-distance, Kirousis et al. [26] developed an optimal power assignment algorithm for strong connectivity in $O(n^4)$ time. In the Euclidean case, [12] obtains constant ratio algorithms for the bounded-hop vertex connectivity for well spread instances. Beier et al. [4] proposed an optimal algorithm to find a bounded-hop minimum energy path between pairs of nodes. In [7] the authors obtain bicreteria approximation algorithms for connectivity and broadcast while minimizing the hop-diameter and energy consumption. Funke and Laue [18] provide a PTAS for the *h*-broadcast algorithm in time linear in *n*. Elkin et al. [16] proposed the solution for the broadcast tree construction (which is easily deformable into the data collection tree) such that the total energy consumption and transport are of factor ρ from optimal bound (which is proportional to the weight of minimal spanning tree for the set of nodes where the weight of edge is defined as the squared Euclidean distance between

 $^{^{2}}$ As described later in the paper, using the Euclidean minimum spanning tree minimizes the energy consumption.

the nodes) and the hop-diameter is $n/\rho + \log \rho$, for any chosen integer parameter $\rho, 1 \le \rho \le n^3$. Additional results for bounded range assignments can be found in [11, 13, 40].

The additional work considering all of three measures has been done by Crowcroft et al. [14]. They [14] have shown two different approaches. The first is based on so-called *balance nodes*, where the main motivation is to build data collection routes based on centrally located nodes in topologies which are already efficient in terms of some of the metrics. In the second approach, they examined the addition of shortcut links to the currently constructed topology in order to allow the required tradeoff between studied criteria. We show, in our simulation scenarios, the comparison between our and the first approach taken in [14] when producing tree T_S with guaranteed hopdiameter $H(T_S) = O(\log n)$ and transport capacity $D(T_S) = O(\log n \cdot w(MST))$, where w(MST)is the weight of minimal spanning tree for our set of nodes, when the edge weight is defined as the Euclidean distance between two nodes. The reason we choose to make this specific comparison lies in the fact that both constructions have logarithmic hop diameter and our goal was to check out the performance of other characteristics.

4. Single-hop collection

We start be defining the notion of geometric centroids and then analyze the performance bounds of single-hop communication backbone which is centroid-based. In the end we discuss the possible pitfalls of using a single-hop collection tree.

For *n* points $P = \{p_1, p_2, \ldots, p_n\}, n \ge 2$, placed in the Euclidean plane, with coordinates (x_i, y_i) , $i = 1, \ldots, n$, and assuming general position, the *centroid* c(P) is a point defined as $c(P) = (\overline{x}, \overline{y})$, where $\overline{x} = \sum_{i=1}^{n} x_i/n$ and $\overline{y} = \sum_{i=1}^{n} y_i/n$, which conceptually represents the center location of *P*.

Apparently the centroid of n points has two very interesting properties as outlined in the following theorems that provide an analysis of the sum of squares of distances, which was done in [28], and sum of distances, which we develop here, between the points and the centroid.

Theorem 4.1 ([28]). For any set of points P and an arbitrary point p' in the Euclidean plane, $\sum_{p \in P} d(p, c(P))^2 \leq \sum_{p \in P} d(p, p')^2.$

Theorem 4.2. For any set of points P and an arbitrary point p' in the Euclidean plane, $\sum_{p \in P} d(p, c(P)) \leq 2 \sum_{p \in P} d(p, p')$.

Proof. Let p^* be the geometric median³ of points P. Clearly for every $p \in P$, $d(p, c(P)) \leq d(p, p^*) + d(p^*, c(P))$, and thus $\sum_{p \in P} d(p, c(P)) \leq \sum_{p \in P} d(p, p^*) + |P| \cdot d(p^*, c(P))$. From the convexity of the Euclidean norm it follows that the norm of an average of a set of points is at most the average of the norms of the points in the set, that is $d(p^*, c(P)) \leq \sum_{p \in P} d(p, p^*)/|P|$. Therefore for any $p' \in R^2$, $d(p^*, c(P)) \leq 2 \sum_{p \in P} d(p, p^*) \leq 2 \sum_{p \in P} d(p, p')$. \blacksquare Clearly, the bounds shown above represent the total energy consumption and transport capacity

Clearly, the bounds shown above represent the total energy consumption and transport capacity measure for a single-hop data collection tree if the base station is located at the centroid of the sensors, which is reasonable to expect.

Unfortunately, if we consider a single-hop tree T_S rooted at the centroid and spanning all the nodes it may be inefficient in terms of energy consumption and transport capacity. Consider the

³The geometric median p^* of a point set P is the point in the Euclidean plane that minimizes the sum of distances between itself and the points in P, i.e. $\forall p' : \sum_{p \in P} d(p, p^*) \leq \sum_{p \in P} d(p, p')$.

linear layout of nodes as depicted at Figure 1. If we consider the minimum spanning tree (MST) of the nodes, we obtain D(MST) = E(MST) = n - 1. On the other hand, for T_S , we have $D(T_S) = \Omega(n^2)$ and $E(T_S) = \Omega(n^3)$, which is quite poor compared to the one obtained by the MST.

In the next section we describe a hierarchical topological structure, the *k*-layer centroid network, which is used for multi-hop data collection in random WSNs and achieves better performance than the single-hop tree.



Figure 1: Worst case performance of single-hop centroid-based data collection tree.

5. Multi-hop collection for random deployments

Our first construction of multi-hop data collection is for randomly deployed sensor networks. In this scenario we assume that n sensor nodes are randomly and independently placed in the area A with uniform distribution. We also assume that A is a unit square. We show an efficient communication backbone construction which is based on *centroid networks*, which are hierarchical geometrical structures on top of a point set P which represents the sensor nodes. As in the single-hop scenario, we assume the base station is located at c(P).

5.0.1. k-layer centroid networks

We start by providing the definitions and notation used in the context of k-layer centroid networks and then proceed to presenting several useful properties and observations regarding these networks.

The k-layer centroid network, k > 2, based on a point set P (in short, k-centroid network), is a k-layer undirected tree $T_P = (V, E)$, where V and E are the node and edge sets, respectively. The leafs of the tree $V_P \subset V$ represent the points P, and the internal nodes $V_C = V \setminus V_P$ represent the centroids of subsets of P. Let r be the root of the tree. For convenience we use the notion of node and point interchangeably instead of saying node that represents a point.

The nodes V are divided into k layers, V_1, \ldots, V_k such that $V_1 = \{r\}$, $V_C = V_1 \cup \ldots \cup V_{k-1}$, and $V_k = V_P$. The edges E connect between nodes in adjacent layers such that the parent of $u \in V_i$, $\pi(u)$, is in V_{i-1} and the children of $v \in V_j$, N(v), are in V_{j+1} , for any $i, j, 1 < i \leq k, 1 \leq j < k$. We use E_i to denote the set of edges between layers i and $i+1, 1 \leq i \leq k-1$. In a k-centroid network the following two conditions hold for any node $v \in V_C$:

- |N(v)| > 0.
- Let T_v be a subtree of T, rooted at $v \in V_C$, and let P_v be the points represented by the leafs of T_v . Then, v is the centroid of P_v .

For example, Figure 2 shows a 3-centroid network where the second layer nodes are centroids of points sets P_1, P_2, P_3, P_4 .



Figure 2: An example of a k-centroid network.

Note that according to the second condition above, the root of the tree is the centroid of the whole point set P. Next we provide several useful properties of k-centroid networks. We start with an observation which follows directly from the definition above.

Observation 5.1. Let T_P be a k-centroid network, k > 2, and let v be a non-leaf node in T_P with a height of l. Then T_v is an (l + 1)-centroid network based on P_v and if l > 1 then for every $u \in N(v)$, T_u is an l-centroid network based on P_u .

Another interesting characteristic of k-centroid networks is that it is possible to easily add or remove layers with only local changes to the edge set E. We refer to the process of adding layers as extension and to the removal of layers as simplification. Let T_P be the original k-centroid network. A simplified network $T_P^{(-i)} = (V^{(-i)}, E^{(-i)})$ is obtained by removing the *i*-th layer, 1 < i < k(the root and the leafs cannot be removed), and connecting the parent of every removed node to its grandchildren in T_P . Formally,

$$V^{(-i)} = V \setminus V_i$$

and

$$E^{(-i)} = (E \setminus E_i) \cup \{(\pi(u), v) : u \in V_i, v \in N(u)\}$$

Adding a layer to **extend the network** is essentially providing an additional level of grouping the points into subsets. To add a layer below an existing *i*-th layer, $1 \le i < k$ (it is not possible to extend the network below the leafs layer), we need to remove the edges that connect layers V_i and V_{i+1} , and to add new edges which connect the new layer to the rest of the tree. Formally, for a *k*-centroid network, the new (k + 1)-centroid network, $T^{(+i)} = (V^{(+i)}, E^{(+i)})$, is defined as follows. For each node $u_j \in V_i$, $1 \le j \le |V_i|$, we partition its children $N(u_j)$ into m_j , $1 \le m_j < |N(u_j)|$ disjoint subsets $U_1^j, \ldots, U_{m_j}^j \subseteq N(u_j)$. Then, the new nodes of the added layer, $V_{[i] \leftrightarrow [i+1]}$, are the centroids of the union of the leafs in the trees rooted at the nodes of these subsets, that is

$$V_{[i]\leftrightarrow[i+1]} = \{u_l^j : 1 \le j \le |V_i|, 1 \le l \le m_j\}$$

where

$$u_l^j = c(\{p : p \in P_v, v \in U_l^j\})$$

The edge set is modified by disconnecting V_i and V_{i+1} and connecting these layers to the new nodes,

$$E^{(+i)} = (E \setminus E_i) \cup \{(u_j, u_l^j) : 1 \le j \le |V_i|, 1 \le l \le m_j\} \\ \cup \{(u_l^j, v) : 1 \le j \le |V_i|, 1 \le l \le m_j, v \in U_l^j\}.$$

The following theorem shows that by extending an existing k-centroid network we actually reduce the sum of squares of distances in the network. For the ease of exposition we denote by d(u, v) the distance between the points or centroids represented by the nodes $u, v \in V$, and by $S_2(T_P)$ the sum of squares of distances in T_P , i.e. $S_2(T_P) = \sum_{(u,v)\in E} d(u,v)^2$.

Theorem 5.2. Let T_P be a k-centroid network based on a point set P. For any l-centroid network, T'_P , which can be obtained through a series of extensions from T_P , it holds that $S_2(T_P) \ge S_2(T'_P)$.

Proof. In order to prove the theorem, it is enough to show that for l = k + 1 it holds $S_2(T_P) \ge S_2(T'_P)$. Let T'_P be obtained from T_P by adding a layer below some existing *i*-th layer, for some $i, 1 \le i < k$. We are going to show, separately for each centroid $u_j \in V_i, 1 \le j \le |V_i|$, that $\sum_{(x_m,y_m)\in N(u_j)}d(u_j, (x_m,y_m))^2 \ge \sum_{l=1}^{m_j}d(u_j, u_l^j)^2 + \sum_{l=1}^{m_j}\sum_{p\in U_l^j}d(u_l^j,p)^2$. Subtract from the left side of the inequality the right side. If the theorem is true, the result should be non-negative. $\sum_{(x_m,y_m)\in N(u_j)}d(u_j, (x_m,y_m))^2 - \sum_{l=1}^{m_j}d(u_j, u_l^j)^2 - \sum_{l=1}^{m_j}\sum_{p\in U_l^j}d(u_l^j,p)^2 = \langle \sum_{l=1}^{m_j}|U_l^j|x_{u_j}^2 - 2\sum_{l=1}^{m_j}|U_l^j|x_{u_j}x_{u_l^j} + \sum_{l=1}^{m_j}|U_l^j|x_{u_j}^2 - \sum_{l=1}^{m_j}x_{u_j}x_{u_l^j} - \sum_{l=1}^{m_j}|U_l^j|x_{u_l^j}^2 - \sum_{l=1}^{m_j}|U_l^j|y_{u_l^j}^2 - \sum_{l=1}^{m_j}|U_l^j|$



Figure 3: Extending a k-network does not always improve the sum of distances.

Unfortunately, we cannot make a similar claim for sum of distances (as demonstrated in Figure 3). Let us consider the set P of k (2a + 2), $k, a \in \mathbb{N}$, points on line, ordered in increasing order by their coordinates x_i , i = 1, ..., n. The distance between points x_i and x_{i+1} , for i = 1, ..., k (2a + 2), $i \neq k$, $i \neq k$ (a + 1), $i \neq k$ (2a + 1), is 1; for i = k (a + 1) it is 2; and for i = k, i = k (2a + 1), it is d. The coordinate of the centroid C of the points in P, is $\overline{x} = k$ (a + 1) - 1 + d. We partition P into two sets: $P_1 = \{x_1, ..., x_{k(a+1)}\}$ and P_2 - the remaining points. Coordinate of the centroid C_1 of the points in P_1 , is $\overline{x}_1 = \frac{k(a+1)^2 + 2ad - 3a - 1}{2(a+1)}$. The sum of the distances between C and the points in P_1 is $\sum_{i=1}^{k(a+1)} (\overline{x} - x_i) = \frac{k^2(a+1)^2 + k(a-1) + 2kd}{2}$. The sum of the distances between C_1 and the points in S_1 is $\sum_{i=1}^{k(a+1)} |\overline{x}_1 - x_i| = \frac{k^2a(a+1) - 2ak + 2akd}{a+1}$. When comparing these two sums one can see that in k(a+1)

the case of a > 1 and for any given k there is such d for which $\sum_{i=1}^{k(a+1)} |\overline{x}_1 - x_i| > \sum_{i=1}^{k(a+1)} (\overline{x} - x_i)$. The same happens with a symmetric case while considering the sum of distances between C and C_2 (the centroid of P_2) and the points of P_2 . Thus, we obtain that the sum of distances from C to the entire set is less than the sum of distances from C_1 to P_1 plus the sum of distances from C_2 to P_2 .

5.1. Data collection using centroid networks

First we describe the k-centroid network T = (V, E) which we then use to produce the communication backbone.

Let P be the points that correspond to the location of sensor nodes S. To construct T we repeatedly divide the unit square area A into sub-areas. First we divide A into 4 equal square sub-areas, then each of these sub-areas is further divided into 4 sub-areas, and so forth. In every sub-area we pick one centroid of the points in that sub-area and add it to T. The connections between these centroids are added according to the point hierarchy as described above, while the root of T is the centroid of all the points P. The iteration proceeds in steps, where at each step we handle subdivision of sub-areas of the same size; it ends once it is not possible to continue subdividing the areas into non-empty square regions. In the final phase, the centroids are connected to the points in their respective areas. We now describe this process in detail.

- 1. Let $j \leftarrow 1$, $\mathcal{A}_1 \leftarrow \{A\}$, $V \leftarrow V_1 \leftarrow \{c(P)\}$, $E \leftarrow \emptyset$.
- 2. While it is possible to divide all the areas in \mathcal{A}_i into 4 non-empty equal square sub-areas:
 - (a) Initialize $\mathcal{A}_{j+1} \leftarrow \emptyset$, $V_{j+1} \leftarrow \emptyset$, $E_j \leftarrow \emptyset$.
 - (b) For every $A' \in \mathcal{A}_i$:
 - i. Let P' be the points which are within area A'.
 - ii. Divide A' into 4 equal square sub-areas A'_1, A'_2, A'_3, A'_4 . Let P'_1, P'_2, P'_3, P'_4 be the points sets in these areas, respectively.

 - iii. Add the centroids $c(P'_1)$, $c(P'_1)$, $c(P'_1)$, and $c(P'_1)$ to V_{j+1} . iv. Add the edges $(c(P'), c(P'_1))$, $(c(P'), c(P'_2))$, $(c(P'), c(P'_3))$, and $(c(P'), c(P'_4))$ to E_j . v. Add the areas A'_1 , A'_2 , A'_3 , and A'_4 to A_{j+1} .
 - (c) Update $V \leftarrow V \cup V_{j+1}$, $E \leftarrow E \cup E_j$, and increase $j \leftarrow j+1$.
- 3. Initialize $V_{j+1} \leftarrow \emptyset$ and $E_j \leftarrow \emptyset$.
- 4. For every $A' \in A_i$:
 - (a) Let P' be the points inside A'.
- (b) Add all the edges $\{(c(P'), p) : p \in P'\}$ to E_j and P' to V_{j+1} .
- 5. Update $V \leftarrow V \cup V_{j+1}$ and $E \leftarrow E \cup E_j$.

For example of an execution, see Figure 4.

Let k be the last value of j in the above scheme. Clearly, the obtained T = (V, E) is a k-centroid network. We are now ready to define the data collection tree $T_S = (S \cup \{r\}, E_S)$. The general idea is to match between the virtual nodes in V and the sensor nodes S. For every centroid $c \in V$, let P_c be the points that produced c, and let S_c be the sensor nodes that correspond to these points. Then we choose $s_c \in S_c$ to be the sensor node which is closest⁴ to c, i.e. $d(s_c) = \min_{s \in S_c} d(s, c)$. Note that we might not have a tree yet, as it is possible that there are cycles and self-loops. These are easily removed by running a breadth-first search in the obtained graph, starting with the root (the node closest to the centroid of all the sensors). The resulting breadth-first tree is T_S .

In order to estimate the efficiency of the constructed data collection tree T_S we will use the following theorems.

⁴The distance between a sensor node and a point is the Euclidean distance between the location of the sensor node and the coordinates of the point in the Euclidean plane.



(a) The single centroid in V_1 .





(d) The 3-centroid network (without links to the points).

Figure 4: An example of the algorithm execution, showing the construction of a 3-centroid network (the links to the points in the last layer are omitted for clarity). The triangles represent the centroids in all three layers.

Theorem 5.3 ([43]). The sum of the of edges of an MST in two (three) dimensional unit size square (cube) for random uniform points is $\Omega(n^{1/2})$ ($\Omega(n^{2/3})$).

Theorem 5.4 ([36], Theorem 2.2). The sum of the squares of edges of an MST in two (three) dimensional unit size square (cube) for random uniform points is $\Omega(1)$ ($\Omega(n^{1/3})$).

We claim the following.

Theorem 5.5. For the data collection tree T_S it holds that $H(T_S) = O(\log n)$, $E(T_S)$ is $O(\log n)$ times the optimal, and $D(T_S)$ is O(1) times the optimal.

Proof. Suppose we run the scheme of constructing T until j = h + 1, $h + 1 \leq k$. In other words we perform step 2 of the scheme h - 1 times and then proceed to step 3. We obtain the h + 1-centroid network. Denote the sum of squares of lengths of edges in E_h by $\sum_{h}^{[2]}$ and the sum of squares of lengths of the edges in $E \setminus E_h$ by $\sum_{c}^{[2]}$. Denote the sum of lengths of edges in E_h by $\sum_{h}^{[2]}$ and the sum of squares of lengths of the edges in $E \setminus E_h$ by $\sum_{c}^{[2]}$. Denote the sum of lengths of edges in E_h by $\sum_{h}^{[2]}$ and the sum of squares of lengths of the edges in $E \setminus E_h$ by \sum_{c} . Obviously, $E(T_S) = \sum_{h}^{[2]} + \sum_{c}^{[2]}$ and $D(T_S) = \sum_{h} + \sum_{c}$. After h - 1 times of A partition, \mathcal{A}_h has 4^{h-1} square sub-areas, each of which has diagonal of length $\sqrt{\frac{2}{|\mathcal{A}_h|}} = \sqrt{\frac{2}{4^{h-1}}}$. Since, each $\mathcal{A}' \in \mathcal{A}_h$ has one centroid (and the total amount of centroids in \mathcal{A}_h is $|V_h| = |\mathcal{A}_h| = 4^{h-1}$), then $\sum_{h}^{[2]} \leq \left(\sqrt{\frac{2}{|\mathcal{A}_h|}}\right)^2 (n - |V_h|) \leq \frac{2}{4^{h-1}} \left(n - 4^{h-1}\right) = O\left(\frac{n}{4^{h-1}}\right)$, and $\sum_t \leq \sqrt{\frac{2}{|\mathcal{A}_h|}} (n - |V_h|) \leq \sqrt{\frac{2}{4^{h-1}}} \left(n - 4^{h-1}\right) = O\left(\frac{n}{\sqrt{4^{h-1}}} \times \frac{1}{\sqrt{n-1}}\right)$.

(c) The centroids V_3 .

By applying the scheme of construction T for this case of sensors arrangement, it is easy to see that $\sum_{c}^{[2]} = O(\log |\mathcal{A}_{h}|) = O(\log 4^{h-1})$ and $\sum_{c} = O(\sqrt{|\mathcal{A}_{h}|}) = O(\sqrt{4^{h-1}})$. Thus, for the case of grid, $E(T_{S}) = \sum_{h}^{[2]} + \sum_{c}^{[2]} = O(\frac{n}{4^{h-1}} + \log 4^{h-1})$ and $D(T_{S}) = \sum_{h} + \sum_{c} = O(\frac{n}{\sqrt{4^{h-1}}} + \sqrt{4^{h-1}})$. Returning to the stochastic case we observe that the sums $\sum_{c}^{[2]}$ and \sum_{c} are maximal, if in each $\mathcal{A}' \in \mathcal{A}_{h}$ there is a sensor. This implies that each $\mathcal{A}' \in \mathcal{A}_{i}$, $i = 1, \ldots, h-1$, is not empty. Therefore, $\sum_{c}^{[2]}$ and \sum_{c} are equal to those on the grid up to a constant, even if we choose the centroids arbitrary within their corresponding sub-area. Thus, $E(T_{S}) = \sum_{h}^{[2]} + \sum_{c}^{[2]} = O(\frac{n}{4^{h-1}} + \log 4^{h-1})$ and $D(T_{S}) = \sum_{h} + \sum_{c} = O(\frac{n}{\sqrt{4^{h-1}}} + \sqrt{4^{h-1}})$. For $h-1 = \log_{4} n$, $E(T_{S}) = O(\log n)$ and $D(T_{S}) = O(\sqrt{n})$. Note that for the random uniform distribution of sensors in A, the algorithm for constructing T stops when the area of square in \mathcal{A}_{h} is at most $O(\frac{\log n}{n})$ [41]. Since $|\mathcal{A}_{h}| \ge \frac{n}{\log n}$, it follows that $k = O(\log \frac{n}{\log n}) = O(\log n)$. Thus, $E(T_{S}) = O(\log n)$ and $D(T_{S}) = O(\sqrt{n})$.

Following Theorems 5.3 and 5.4, we conclude that $E(T_S)$ is $O(\log n)$ times the optimal, and $D(T_S)$ is O(1) times the optimal solution.

Suppose that the sensors are uniformly distributed within a unit cube. According to the scheme, similar to the above, we can build the *k*-centroid network, $k = O(\log n)$. Following the assumptions and arguments similar to the above, it can be shown, that $\sum_{h}^{[2]} = O\left(\frac{n}{\sqrt[3]{(8^{h-1})^2}}\right)$, $\sum_{h} = O\left(\frac{n}{\sqrt[3]{(8^{h-1})^2}}\right)$, and $\sum_{c}^{[2]} = O\left(\sqrt[3]{(8^{h-1})^2}\right)$, $\sum_{c} = O\left(\sqrt[3]{(8^{h-1})^2}\right)$. Thus, $E(T_S) = \sum_{h}^{[2]} + \sum_{c}^{[2]} = O\left(\frac{n}{\sqrt[3]{(8^{h-1})^2}}\right)$ and $D(T_S) = \sum_{h} + \sum_{c} = O\left(\frac{n}{\sqrt[3]{(8^{h-1})^2}} + \sqrt[3]{(8^{h-1})^2}\right)$. For $h - 1 = \log_8 n$,

 $E(T_S) = O(\sqrt[3]{n})$ and $D(T_S) = O(\sqrt[3]{n^2})$. Using the results of Theorems 5.3 and 5.4, we obtain that for three-dimensional case $E(T_S)$ and $D(T_S)$ are O(1) times the optimal solution.

One can wonder whether the idea of routing all data through central nodes would generate a congestion points in the network backbone and also influence the on the lifetime of the network. First, we observe that in our centroid-based construction the average squared edge's length is O(1) which compares well with the similar bound for MST, see Zhang and Hou [50]. It means that it terms of lifetime, we would expect the good performance of our solution. Regarding the congestion points, a good synchronization and scheduling mechanism, for example see algorithm Time-Slots for tree proposed by [17], efficiently deals with the problem. In particular, each node in the tree keeps the total number d of its siblings (having the same parent) and it's sequential number between the ordering of siblings. Then this node is allowed to send a message to its parent if the time slot is equal to the sequential number of the node modulo the total number of siblings.

The distributed implementation of the k-centroid network is quite straightforward once we established connectivity between the nodes and chose the leader (the root of the tree). In order to establish connectivity we can use 2 different approaches. The first, described in Dolev et al. [15] forms a temporary underlying topology in O(n) time using $O(n^3)$ message. The second (better) approach is given by Halldórsson and Mitra [21] that show how to do this in $O(poly(\log \beta, \log n))$, where β is the ratio between the longest and shortest distances among nodes. After the topology is established, we can use leader-election algorithm by Awerbuch [3] that shows how to find a leader in a distributed fashion in a network with n nodes in O(n) time using $O(n \log n)$ messages. Next, using the location of every node, the root of k-centroid network can be determined and the construction of the k-centroid network is started in recursive fashion that takes O(k) time and O(n) messages assuming omnidirectional communication.

6. Multi-centers for arbitrary deployments

The construction of our data collection tree is based on finding a Hamiltonian circuit in the network. The existence of Hamiltonian circuit is evident since graph G represents a full graph (all the nodes potentially capable transmitting to each other). The Hamiltonian circuit is built on top of a minimal spanning tree of the graph, based on an algorithm presented by Andreae and Bandelt [2]. Following the algorithm, we build in linear time a Hamiltonian circuit with the following properties:

Theorem 6.1 ([2]). Let h be a Hamiltonian circuit of graph G, built over the minimal spanning tree of G, T_{MST} . The following applies:

- 1. $W(h) = O(W(T_{MST})).$
- 2. $w(e^{*}(h)) = O(w(e^{*}(T_{MST}))).$

where W(g) is the **weight** of some graph g, calculated as the energy consumption of all the edges in the graph, and $e^*(g)$ is the **longest edge** in graph g.

For full algorithm description and further information see [2] and [16]. Let k, d be natural numbers such that $n = k^d$. We assign indexes to the nodes of circuit $h = \{u_1, u_2, ..., u_n\}$, which consist of vectors $v_i \in V : S \to \mathbb{R}^d$ such that each vector consists of values in range $v_i = (a_1, ..., a_d), 0 \leq a_j \leq k - 1, 1 \leq j \leq d$. Subsequent nodes in the Hamiltonian circuit will receive subsequent vector indexes (e.g. for k = 2, d = 2 $\{u_1, ..., u_4\} = \{00, 01, 10, 11\}$). In fact, parameter d defines the number of centers that we will be using in the construction of our data collection tree.



Figure 5: [k=3,d=3] Index Labeling based on Hamiltonian Circuit Order.

Next, starting at empty graph $\overline{K_n}$, we add an edge between every pair of nodes with indexess subject to $(a_1, ..., a_j, 0, ..., 0)$ and $(a_1, ..., a_j - 1, 0, ..., 0)$ for some $j \in [1, d]$, resulting in graph $T_{k,d}$.



Figure 6: Tree construction example for k = 3, d = 3.

Theorem 6.2. $T_{k,d}$ is a spanning tree of G.

Proof. Since by definition, every node is connected to the node with the last non-zero member of index vector decremented (except node $v_0 = (0, ..., 0)$ which is connected as well), every node in G has at least one edge. Hence, $T_{k,d}$ is a spanner. Next, we count the number of edges, created by the change of each a_i member of index vector. a_1 affects k - 1 edges: (0, 0, ..., 0) - (k - 1, 0, ..., 0). a_2 affects $k \cdot (k-1)$ edges: $(a_1, 0, 0, ..., 0) - (a_1, k-1, 0, ..., 0)$, while $a_1 \in [0, k]$. Consequently, the total number of edges created as a result of using the algorithm: $\sum_{i=0}^{d-1} (k-1) \cdot k^i = (k-1) \frac{k^d-1}{k-1} = n-1$. Since $T_{k,d}$ spans G, $T_{k,d}$ is a spanning tree.

Theorem 6.3. Let $T_{k,d}$ be a tree constructed by the upper mentioned method. The following bounds apply for $T_{k,d}$:

- 1. *Hop-Diameter:* $H(T_{k,d}) = 2(k-1) \cdot d$.
- 2. Energy Consumption: $W(T_{k,d}) = O(\frac{n}{k} \cdot W(T_{MST})).$
- 3. Transport Capacity: $D(T_{k,d}) = O(d \cdot D(T_{MST})).$

Proof.

- 1. Diameter bound. In order to traverse from some node $(a_1, ..., a_d)$ to node v_0 we need to traverse from each node with $(a_1, ..., a_{j-1}, a_j, 0, ..., 0)$ to $(a_1, ..., a_{j-1}, 0, 0, ..., 0)$ which is up to k 1 hops. Since $1 \le j \le d$, the maximal number of hops to node v_0 is d(k-1), hence diameter is 2d(k-1).
- 2. Energy Consumption bound. We assume that the distance between every two adjacent nodes in the Hamiltonian circuit is bounded by $l = O(e^*(T_{MST}))$, and thus require $O(l^2)$ energy to communicate. We sum up all of the edges' energy consumption, by iteratively summing up the edges in each dimension $1 \le j \le d$: $W(T_{k,d}) = \sum_{e \in E(T_{k,d})} d(e) = \sum_{j=1}^d \sum_{e \in E(dimj)} d(e)$. Each dimension j contains $(k-1)k^{j-1}$ edges, each $O(k^{d-j} \cdot l)$ long and consumes $O((k^{d-j})^2 \cdot l^2)$ energy. Hence,

$$W(T_{k,d}) = \sum_{j=1}^{d} (k-1) \cdot k^{j-1} (k^{d-j})^2 \cdot l^2 = l^2 (k-1) \cdot k^{2d-1} \sum_{j=1}^{d} (\frac{1}{k})^j =$$

= $l^2 (k-1) \cdot k^{2d-1} (\sum_{j=0}^{d} (\frac{1}{k})^j - 1) = l^2 (k-1) \cdot k^{2d-1} (\frac{(\frac{1}{k})^{d+1} - 1}{1/k - 1} - 1) =$
= $l^2 \cdot k^{2d} (k^{-1} - k^{-(d+1)}) = l^2 \cdot O(k^{2d-1}) = O(l^2 \cdot \frac{n^2}{k}) =$
= $O(\frac{n}{k} \cdot W(T_{MST}))$

 3. Transport Capacity bound. Transport capacity is measured by the total distance traveled by information when transmitted by all nodes simultaneously. Thus, the metric depends on the total sum of edges' lengths, which we sum up by grouping them into dimensions, similarly to before.

$$D(T_{k,d}) = \sum_{j=1}^{d} (k-1) \cdot k^{j-1} k^{d-j} \cdot l = (k-1)l \cdot \sum_{j=1}^{d} k^{d-1} =$$

= $(k-1) \cdot l \cdot k^{d-1} \cdot d = \frac{k-1}{k} \cdot l \cdot n \cdot d = O(l \cdot n \cdot d) =$
= $O(d \cdot D(T_{MST}))$

Corollary For $k = \frac{n}{\log n}$ and $d = \frac{\log n - \log \log n}{\log n} = O(1)$ we get the following bounds:

- 1. Hop-Diameter: $H(T_{k,d}) = O(\frac{n}{\log n}).$
- 2. Energy Consumption: $W(T_{k,d}) = O(\log n \cdot W(T_{MST})).$
- 3. Transport Capacity: $D(T_{k,d}) = O(D(T_{MST}))$.

Notice, that these results beat the results of Elkin et al. [16] that for logarithmic hop-diameter data collection tree (having the same energy performance bounds) achieved logarithmic factor approximation for transport measure, opposite to our constant factor approximation.

Comparing the obtained results with the centroids-based approach for the uniform random deployment, we can conclude that for similar transport and energy performance for both arbitrary and unform cases, we can build better hop-diameter $O(\log n)$ data collection tree for uniform case than for arbitrary case $(O(n/\log n))$.

7. Simulation results

In this section we show some simulation results of the k-centroid network constructed for the multi-hop random scenario as described in Section 5. As we show, the simulation results fully support and even slightly outperform our theoretical analysis. In what follows we compare the k-centroid network topology with the optimal one, in terms of both energy consumption, hop-diameter and total link distance, which is achieved by using the minimum spanning tree and balance nodes partition based hierarchical tree as the delivery trees. The optimality of MST is straightforward in the case of total distances, whereas for energy consumption it was shown to be the best possible in [38].

In our experiments we have randomly and uniformly distributed n sensor nodes in a unit square, with the network size n ranging from 100 to 5000 in steps of 100. We have computed the total distance of the communication links (Figure 7), the energy consumption (Figure 8), and the hopdiameter (Figure 9) and the weight of the maximal edge of all three topologies. While transport, energy and hop-diameter parameters are natural for evaluation, we choose to evaluate the weight of the maximal edge since the network lifetime (in case of equal initial capacities of all sensors) is heavily depends on this measure. The results below are an average of 20 tries for every network size n.

In terms of total distance (Figure 7), our solution is consistently within a factor less than 2 from the best possible (MST), which matches the theoretical result of the O(1) approximation



Figure 7: Total link distances, $D(\cdot)$.



Figure 8: Total energy consumption (sum of square of distances), $E(\cdot)$.

ratio. Moreover, our algorithm performance beats the performance of the balanced tree solution proposed in [14].

Interestingly, the energy consumption of our scheme (Figure 8) slightly outperforms the pro-

jected theoretical bound of $O(\log n)$, with the ratio rising from 3-4 for smaller networks and u_p^{10} to 6 for larger ones with $n \ge 3000$. As for previous metric, our algorithm again outperforms the solution given in [14]. The practical meaning of the obtained results is that the theoretical bound obtained by us might not optimal and be even decreased by more delicate analysis.



Figure 9: Max hop-distance from every sensor to the root, $H(\cdot)$.

The hop-diameter of our scheme is very close to the optimum (which is obviously 1), being only 8 for a 4000-node WSN. We have used a logarithmic scale in (Figure 9) to compare it to the one produced by MST, which is 10-15 times greater than ours for small networks (*n* from 100 to 700), and as high as 30 times greater for larger ones ($n \ge 700$). The balanced tree approach explained in [14] also produces good results but still produces worse values than ours.

The length of maximal edge is obviously optimal for MST. As we can learn from the Figure 10, our solution again outperforms balanced tree approach in [14] and lies within the small constant factor for different size networks. This compares well with our analysis for the lifetime of the networks where we show that the average length of the edge in the centroids-based construction is similar to the average length of the edge's length in MST. Moreover, we also have checked the values of maximal edge for the arbitrary (opposite to uniform) deployment of sensor nodes. The results are shown in Figure 11.

From Figure 11 we can see the similar performance as was obtained for the uniform distribution of nodes. It means that the deployment (almost) does not influence the performance of our proposed construction.

8. Conclusions

In this paper we developed various data collection topologies that were based on the location theory notion of centroids and central nodes. We have shown that a centroids based hierarchy



Figure 10: The length of maximal edge for uniform deployment.



Figure 11: The length of maximal edge for arbitrary deployment.

provides good approximation factor solutions for energy, transport capacity, and hop-diameter measures, in 2D, and performs asymptotically optimal in 3D for random sensors locations. Our simulation results verify our theoretical findings and, in fact, suggest that a possible tighter analysis

for two dimensional space may exist. We also presented a construction for arbitrary deployment based on central nodes of the network that performs well for our desired measures. It would also be interesting to investigate the construction, where one of the objectives is an average hop-count between the nodes in the obtained network.

References

- Ian F. Akyildiz, Weilian Su, Yogesh Sankarasubramaniam, and Erdal Cayirci. Wireless sensor networks: a survey. *Computer Networks*, 38(4):393–422, 2002.
- [2] Thomas Andreae and Hans-Jürgen Bandelt. Performance guarantees for approximation algorithms depending on parametrized triangle inequalities. SIAM J. Discrete Math., 8(1):1–16, 1995.
- [3] B. Awerbuch. Optimal distributed algorithms for minimum weight spanning tree, counting, leader election, and related problems. In ACM STOC 1987, pages 230–240, 1987.
- [4] Rene Beier, Peter Sanders, and Naveen Sivadasan. Energy optimal routing in radio networks using geometric data structures. In *ICALP'02*, pages 366–376, 2002.
- [5] Daniel Berend, Michael Segal, and Hanan Shpungin. Energy and lifetime efficient connectivity in wireless ad-hoc networks. Ad Hoc & Sensor Wireless Networks, 10(1):61-87, 2010.
- [6] Gruia Calinescu, Sanjiv Kapoor, Alexander Olshevsky, and Alexander Zelikovsky. Network lifetime and power assignment in ad hoc wireless networks. In ESA'03, pages 114–126, 2003.
- [7] Gruia Calinescu, Sanjiv Kapoor, and M. Sarwat. Bounded-hops power assignment in ad hoc wireless networks. *Discrete Applied Mathematics*, 154(9):1358–1371, 2006.
- [8] A. Chandrakasan, R. Amirtharajah, S. Cho, J. Goodman, G. Konduri, J. Kulik, W. Rabiner, and A. Wang. Design considerations for distributed microsensor systems. In *CICC'99*, pages 279–286, 1999.
- [9] Jae-Hwan Chang and Leandros Tassiulas. Energy conserving routing in wireless ad-hoc networks. In *INFOCOM'00*, pages 22–31, 2000.
- [10] Ying-Ju Chen and Jin-Fu Chang. Per connection performance analysis of a frame-based TDMA/CDMA MAC protocol containing both reservation and contention slots. *Queueing* Syst., 49(2):123–159, 2005.
- [11] Andrea E. F. Clementi, Alfonso Ferreira, Paolo Penna, Stephane Perennes, and Riccardo Silvestri. The minimum range assignment problem on linear radio networks. In ESA '00, pages 143–154, 2000.
- [12] Andrea E. F. Clementi, Paolo Penna, and Riccardo Silvestri. On the power assignment problem in radio networks. *Electronic Colloquium on Computational Complexity*, 7(054), 2000.
- [13] Andrea E. F. Clementi, Paolo Penna, and Riccardo Silvestri. The power range assignment problem in radio networks on the plane. In STACS'00, pages 651–660, 2000.

- [14] Jon Crowcroft, Michael Segal, and Liron Levin. Improved structures for data collection in wireless sensor networks. In 2014 IEEE Conference on Computer Communications, INFOCOM 2014, Toronto, Canada, April 27 - May 2, 2014, pages 1375–1383, 2014.
- [15] S. Dolev, M. Segal, and H. Shpungin. Bounded-hop energy-efficient liveness of flocking swarms. *IEEE Transactions on Mobile Computing*, 2012, to appear.
- [16] Michael Elkin, Yuval Lando, Zeev Nutov, Michael Segal, and Hanan Shpungin. Novel algorithms for the network lifetime problem in wireless settings. 17(2):397–410, 2011.
- [17] Pierre Fraigniaud, Andrzej Pelc, David Peleg, and Stephane Perennes. Assigning labels in an unknown anonymous network with a leader. *Distributed Computing*, 14(3):163–183, 2001.
- [18] Stefan Funke and Soren Soren Laue. Bounded-hop energy-efficient broadcast in lowdimensional metrics via coresets. In STACS'07, volume 4393, pages 272–283, 2007.
- [19] Naveen Garg and Jochen Könemann. Faster and simpler algorithms for multicommodity flow and other fractional packing problems. In FOCS'98, pages 300–309, 1998.
- [20] Piyush Gupta and P. R. Kumar. The capacity of wireless networks. *IEEE Transactions on Information Theory*, 46(2):388–404, 2000.
- [21] Magnús M. Halldórsson and Pradipta Mitra. Distributed connectivity of wireless networks. In PODC, pages 205–214, 2012.
- [22] Özlem Durmaz Incel, Amitabha Ghosh, Bhaskar Krishnamachari, and Krishna Chintalapudi. Fast data collection in tree-based wireless sensor networks. *IEEE Trans. Mob. Comput.*, 11(1):86–99, 2012.
- [23] Ozlem Durmaz Incel and Bhaskar Krishnamachari. Enhancing the data collection rate of tree-based aggregation in wireless sensor networks. In SECON'08, pages 569–577, 2008.
- [24] Aleksandar Jovicic, Pramod Viswanath, and Sanjeev R. Kulkarni. Upper bounds to transport capacity of wireless networks. *IEEE Transactions on Information Theory*, 50(11):2555–2565, 2004.
- [25] Konstantinos Kalpakis, Koustuv Dasgupta, and Parag Namjoshi. Efficient algorithms for maximum lifetime data gathering and aggregation in wireless sensor networks. *Computer Networks Journal*, 42(6):697–716, 2003.
- [26] Lefteris M. Kirousis, Evangelos Kranakis, Danny Krizanc, and Andrzej Pelc. Power consumption in packet radio networks. *Theoretical Computer Science*, 243(1–2):289–305, 2000.
- [27] K.Ramanan and E.Baburaj. Data gathering algorithms for wireless sensor networks: A survey. *IJASUC*, 1, December 2010.
- [28] Amit Kumar, Yogish Sabharwal, and Sandeep Sen. Linear-time approximation schemes for clustering problems in any dimensions. *Journal of the ACM*, 57(2):1–32, 2010.
- [29] Liron Levin, Michael Segal, and Hanan Shpungin. Optimizing performance of ad-hoc networks under energy and scheduling constraints. In WiOpt'1-, pages 11–20, 2010.

- [30] Weifa Liang and Yuzhen Liu. Online data gathering for maximizing network lifetime in sensor networks. *IEEE Transactions on Mobile Computing*, 6(1):2–11, 2007.
- [31] Ariel Orda and Ben-Ami Yassour. Maximum-lifetime routing algorithms for networks with omnidirectional and directional antennas. In *MobiHoc'05*, pages 426–437, 2005.
- [32] Kaveh Pahlavan and Allen H. Levesque. Wireless information networks. Wiley-Interscience, 1995.
- [33] J. Park and Salim Sahni. Maximum lifetime broadcasting in wireless networks. *IEEE Trans*actions on Computers, 54(9):1081–1090, 2005.
- [34] Venkatesh Rajendran, Katia Obraczka, and J. J. Garcia-Luna-Aceves. Energy-efficient collision-free medium access control for wireless sensor networks. In SenSys'03, pages 181– 192, 2003.
- [35] Ram Ramanathan and Regina Hain. Topology control of multihop wireless networks using transmit power adjustment. In *INFOCOM'00*, pages 404–413, 2000.
- [36] C. Redmond and J.E. Yukich. Asymptotics for euclidean functionals with power-weighted edges. Stochastic Processes and their Applications, 61(2):289 – 304, 1996.
- [37] Michael Segal. Fast algorithm for multicast and data gathering in wireless networks. Information Processing Letters, 2007.
- [38] Michael Segal and Hanan Shpungin. On construction of minimum energy k-fault resistant topology. Ad Hoc Networks, 7(2):363–373, 2009.
- [39] Hanan Shpungin. Energy efficient online routing in wireless ad hoc networks. In SECON'11, pages 64–72, 2011.
- [40] Hanan Shpungin and Michael Segal. Low-energy fault-tolerant bounded-hop broadcast in wireless networks. *IEEE/ACM Trans. Netw.*, 17(2):582–590, 2009.
- [41] Hanan Shpungin and Michael Segal. Near optimal multicriteria spanner constructions in wireless ad-hoc networks. *IEEE/ACM Transactions on Networking*, 18(6):1963–1976, 2010.
- [42] Jeffrey Stanford and Sutep Tongngam. Approximation algorithm for maximum lifetime in wireless sensor networks with data aggregation. In SNPD'06, pages 273–277, 2006.
- [43] J. Michael Steele. Probability and problems in euclidean combinatorial optimization. Statistical Science, 8(1):48 – 56, 1993.
- [44] Lu Su, Yan Gao, Yong Yang, and Guohong Cao. Towards optimal rate allocation for data aggregation in wireless sensor networks. In *Mobihoc'11*, pages 1–11, 2011.
- [45] L.F.W. van Hoesel and P.J.M. Havinga. A lightweight medium access protocol (lmac) for wireless sensor networks:reducing preamble transmissions and transceiver state switches. In *INSS*'04, pages 205–208, 2004.
- [46] Yafeng Wu, John A. Stankovic, Tian He, and Shan Lin. Realistic and efficient multi-channel communications in wireless sensor networks. In *INFOCOM'08*, pages 1193–1201, 2008.

- [47] Liang-Liang Xie and Panganamala R. Kumar. A network information theory for wireless com²¹ munication: scaling laws and optimal operation. *IEEE Transactions on Information Theory*, 50(5):748–767, 2004.
- [48] Liang-Liang Xie and Panganamala R. Kumar. On the path-loss attenuation regime for positive cost and linear scaling of transport capacity in wireless networks. *IEEE Transactions on Information Theory*, 52(6):2313–2328, 2006.
- [49] Feng Xue, Liang-Liang Xie, and Panganamala R. Kumar. The transport capacity of wireless networks over fading channels. *IEEE Transactions on Information Theory*, 51(3):834–0847, 2005.
- [50] Honghai Zhang and Jennifer C. Hou. Asymptotic critical total power for k-connectivity of wireless networks. *IEEE/ACM Trans. Netw.*, 16(2):347–358, 2008.